

MINMATIC		DESCRIPTION						
	6 stations / 5 colors Machine							
1	Total diameter	300 cm						
2	Base diameter	118 cm						
3	Total weight	1160 kg						
4	High	160 cm						
5	Air consumption / pressure	450 l/min, 6 bar(90psi)						
6	Electrical requirements	230V, 1PH, 60W, 1A						
7	Max PRINT area	16" x 16"						
8	Direction	one side (CCW)						
9	Max print speed	900 cycle/hour						
10	Squeegee & Flood speed	Independent for each printing head						
11	Warranty	2 years limited warranty						
12	Multi print	Multiple print for chosen print head						
13	Special option	For multiple print there is possible to set table in up position for every multiple print or set to move table every one print						
14	Test print	Possibility to run press in test print mode for individual print head or for all colors						
15	Free wheel	Possibility to unlock indexer to move lower wheel with table by hand						
16	Max Screen Size	Size 56 x 80 cm						
17	Programing machine cycle	Possibility to program for special sequence printing system						
	MACHINE	E Q U I P M E N T I N	STANDA	A R D				
18	Pneumatic INDEX	Precision rotation system	1		INCLUDED			
19	Pneumatic Print Heads	Driven by pneumatic pistons, with speed control in both directions	5		INCLUDED			
20	Pneumatic lift	Pneumatic cylinder 4"	1		INCLUDED			
21	Central OFF Contact	Manual off-contact change	1		INCLUDED			
22	Screen AIR locking / per head	Four pneumatic cylinder per screen, manually switched	Option		OPTION			

MiniMatic 6s 5c

23	Skip Switch	On the control panel	1		INCLUDED
24	Quick change Slide Mount platen system	Easy & fast to change platens	6		INCLUDED
25	Pneumatic fasten Squeegee & Flood	Pneumatic system to realize SQ & FL fasten	N/A		N/A
26	Foot Pedal	Let you to control the press	1		INCLUDED
27	Main air regulator with water filter, oil lubrication	Easy to control and service air pressure with oil tank to keep all pneumatic parts in good condition	1		INCLUDED
28	Side (left & right) screen holders	More accessible to put each size of screen onto screen holder	5		INCLUDED
29	Micro Adjustment	Very precision screen's micro registration	5		INCLUDED
30	Micro Dial Indicator	Simple indicator to see any adjustments	5		INCLUDED
31	Rotatable control panel	gives all head control access	1		INCLUDED
32	load and unload safety System	Electric safety bars protecting load and unload positions while machine's rotation	1 set		INCLUDED
33	Print head reduction	- € 600 for take off print head; additional head in the future cost 2600€	Choice		See below
34	1set FREE Squeegee/Flood	16 " length	1		INCLUDED
35	1set FREE Pallets	aluminum rubber coated; size 16" x 22 "	1		INCLUDED
	МАСНІΝЕ	EQUIPMENT IN	OPTIO	N	
36	Pneumatic fasten Squeegee & Flood	+ €200 per print head	0		
37	1 set extra aluminum pallets cm	Aluminum rubber coated; size cm	0		
38	1 set extra squeegee with blade 70 durometer	The length cm	0		
39	1 set extra aluminum flood bar	The length cm	0		
40	Foot Pedal	Let you to control the press by foot switch	0		
41	Printing head reduction on the press	Reduction printing heads relation to standard size	0		
42	CPM-1618 ceramic panel heater	Ceramic panel heater with temperature control, 3 kW, 16A, 230 V	0		
43	CPM-1618-C ceramic panel heater	Ceramic panel heater with temperature control and air flow, 8 kW, 16A, 400 V	0		
44	STAND for QLH/CLH 1618	Adjustable high and angle, isolates flash from press	0		

MiniMatic 6s 5c

45	IR Carbon Quartz Flash CLH 1618	Quartz carbon heater, heat area 16 x 18", Electronic power control, pallet temperature sensor, temperature setting and reading max power 12 kW (auto or manual control)	0	
46	IR Quartz Flash QLH 1618	Quartz Infrared heater, heat area 16 x 18", Electronic power control, max power 12 kW (auto or manual control)	0	